

We Claim:

1. A coupler for joining a first conduit having a first diameter and a second conduit, the first conduit having an axis and a first outwardly extending flange having a second diameter axially spaced from a second outwardly extending flange having a third diameter, the coupler comprising:

- a housing including an annular hole having an outer diameter and an inner diameter; the outer diameter of the annular hole being greater than the second diameter of the first outwardly extending flange;
- the inner diameter of the annular hole being greater than the first diameter of the first conduit, to permit axial movement of the coupler over the first conduit;
- the inner diameter of the annular hole being less than the second diameter of the first outwardly extending flange and less than the third diameter of the second outwardly extending flange to prohibit movement of the portions of the housing defining the annular hole axially along the first conduit over either of the first outwardly extending flange and the second outwardly extending flange;
- the housing and the annular hole being formed with at least two sectors radially compressible into a snap fit relationship with the portions of the sectors defining the annular hole disposed between the first outwardly extending flange and the second outwardly extending flange; whereby
- the coupler is moveable over the first outwardly extending flange to engage the second conduit, with a portions of the sectors defining the annular hole disposed between the first outwardly extending flange and the second outwardly extending flange.

1 2. A coupler in the form of a housing having opposite end faces, the coupler for
2 joining two conduits together, wherein the coupler comprises:

3 an annular hole extending along an axis between said opposite end faces of the
4 housing, the annular hole comprising a first inner diameter, lugs having a second inner
5 diameter, and a flange having a third inner diameter, wherein the first diameter is greater
6 than the second diameter, and the second diameter is greater than the third diameter;

7 the housing comprising a plurality of sectors that snap together; and

8 the plurality of sectors being identical to each other in shape and size.

1
1 3. The coupler of claim 2, wherein the sectors are sufficiently resilient to enable
2 snap lock action in a relative radially inward direction between said plurality of sectors.

1
1 4. The coupler of claim 2, wherein at least one stopping flange is located at an end
2 face of each of the sectors and engages an end face of another of the sectors and
3 prevents relative axial movement between the sectors in first and second axial directions.

1 5. The coupler of claim 4, wherein each sector has an additional said stopping
2 flange preventing relative movement between the sectors.

1 6. A coupler in the form of a nut having an annular hole extending between end
2 faces and centered on an axis, the coupler being adapted for coupling two conduits
3 together by a bayonet twist and lock action, comprising:

4 two sectors of the nut forming having portions defining the annular hole and for
5 surrounding ends of the two conduits by respective axial ends adjacent end faces of the
6 nut;

7 the sectors being sufficiently resilient to snap lock together; wherein

8 the sectors snap lock together by relative radially inward movement.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

7. The coupler of claim 6, comprising at least one axially elongate rib forming a
radially outwardly facing groove and a another axially elongate rib forming a radially
inwardly facing groove on each of the two sectors, wherein the ribs resiliently slide over
each other into a seated position during a snap locking action of the two sectors.

8. The coupler of claim 7, wherein the sectors may be resiliently pried and
separated with a sharp blade of a common tool after the snap locking action.

9. The coupler of claim 7, wherein the ribs prevent relative movement of the two
sectors in a plurality of radial directions.

1 ~~Sub A5~~ 10. A coupler in the form of a nut, the nut having two end faces and an annular hole
2 extending between the two end faces along an axis, the coupler comprising:
3 the nut having two separable sectors joined along mating surfaces, the mating
4 surfaces comprising a portion defined by a set of lines parallel to the axis of the annular
5 hole and a portion perpendicular to said axis; and
6 wherein the portion of said mating surfaces defined by lines parallel to the axis
7 prevents relative movement of the sectors in a plurality of radial directions and the portion
8 of said mating surfaces that is perpendicular to said axis prevent relative movement of the
9 sectors in a plurality of axial directions when said sectors are assembled together.

11. A coupler for coupling two conduits together by a bayonet twist and lock action
2 comprising: two sectors forming respective first and second sectors of a nut and defining
3 an annular hole for surrounding ends of the two conduits, wherein each of the two sectors
4 has means for preventing movement of the first sector relative to the second sector in a
5 first axial direction and means for preventing movement of the first sector relative to the
6 second sector in a second axial direction.

12. A coupler for coupling two conduits together by a bayonet twist and lock action
2 comprising:
3 a nut having an annular hole extending axially between two end faces, the nut
4 having portions defining the annular hole, said portions comprising an inwardly extending
5 flange for rotational retention on a first of said two conduits, said portions having lugs
6 protruding radially inwardly thereon for sliding past bosses of a second of said two conduits
7 in bayonet twist action; wherein

the coupler comprises a locking flange protruding axially from an end face of the coupler, said locking flange having a socket adapted to engage a protrusion on the second of the two conduits for bayonet lock action.

13. A pipe combination, comprising:

a first pipe having a first end with a first bayonet tube disposed at the first end;

a second pipe having a second end with an annular space defined between a first annular flange and a second annular flange, the first annular flange having a diameter greater than the diameter of the annular space;

a pipe coupler having a wall with an axial bore extending between opposing first and second faces, the axial bore having a diameter;

first portions of the coupler extending into the bore at the first face, the first portions having a diameter greater than the diameter of the annular space and less than the diameter of the first flange;

second portions of the coupler extending into the bore and forming a second bayonet tube;

the coupler being adapted for disposition at an operative site with the first portions of the coupler disposed in the space of the first pipe;

the coupler being rotatable at the operative site to engage the first bayonet tube with the second bayonet tube and to draw the second end of the second pipe into fluid communication with the first end of the first pipe; and

the coupler being formed in at least two separate parts adapted to be radially snap fit to form the coupler at the operative site.

1 ~~Sub A6~~ 14. A combination, comprising:

2 (a) a first conduit having an outwardly extending flange on an end of the first
3 conduit,

4 (b) a second conduit having bosses or threads extending radially outward on an end
5 of the second conduit,

6 (c) a coupler forming an annular hole, coupler having portions defining said annular
7 hole, said portions having an inwardly extending flange that receives and holds the
8 outwardly extending flange on the end of the first conduit and lugs or threads that couple to
9 the bosses or threads on the end of the second conduit for a coupled configuration; and

10 wherein the coupler comprises two sectors connected in fixed relation by relative
11 radial movement in a snap lock action.

12 15. The combination of claim 14, wherein the first conduit has a second outwardly
13 protruding flange that prevents axial movement of the coupler along the first conduit.

14 ~~Sub A7~~ 16. The combination of claim 14, wherein the two sectors snap locking together with
15 said portions defining the annular hole surrounding the first conduit and retained thereon by
16 interference of the flanges

17 17. The coupler and conduits combination of claim 16, further comprising ribs and
18 grooves on the two sectors, wherein ribs seat in grooves in the fixed relation and limit radial
19 movement in a plurality of directions, and wherein the first conduit stops relative radial
20 movement of the two sectors in all remaining directions.

1 18. The coupler and conduits combination of claim 16, wherein:

2 the first conduit has a nipple on the end; and

3 the nipple is surrounded by the coupler.

1
1 ~~Sub A-8~~ 19. A method of using a coupler in the form of a nut having a first sector and a
2 second sector defining an annular hole extending between end faces of the nut, the
3 coupler being adapted for coupling a first and a second conduit together, the method
4 comprising the steps of:

5 (a) separating said first and the second sectors of the coupler sufficiently to receive
6 the first conduit,

7 (b) surrounding an outwardly extending flange of the first conduit by portions of the
8 sectors defining said annular hole,

9 (c) flexibly forcing the sectors radially inwardly to a snap lock configuration, wherein
10 the first and second sectors of the coupler form said nut and surround the first conduit, and

11 (d) moving the coupler axially and rotationally with respect to the second conduit
12 thereby coupling the second conduit to the first conduit

1
1 20. The method of using of claim 19 wherein the step of flexibly forcing the sectors
2 radially inwardly further comprises:

3 (a) locating a first rib of the first sector in a second groove of the second sector,

4 (b) hinging the first sector relative to the second sector about said first rib radially
5 inwardly to engage the second sector, and

- 6 (c) snapping a second rib of said first sector into a first groove of the second sector
- 7 at a location diametrically opposite said first rib and said second groove relative to said
- 8 annular hole.